

WOS designed, engineered and manufactured drilling and milling bits

PulverizR™ PDC Bits





Designed with total operation in mind



🚺 About This Product

The WOS line of PulverizR PDC bits cover a wide range of operation types from conventional drilling to unconventional drillouts. Bits engineered and manufactured 100% in house by WOS are designed for long service time and high working efficiency in various downhole environments. Eliminating the risk of losing a cone, these fixed bits are engineered for performance, consistency and durability. Available in several configurations including tubing remediation, frac plug removal and formation drilling.



Benefits

- No moving parts eliminates cones left downhole
- No rev limit allows to drill further longer
- Effective in both stickpipe drill string and coiled tubing conveyance
- Available as a thru tubing, drilling and cleanout options - 1.71" - 17.5"



Eliminates risk of losing cones

Contact Sales: 346-774-4433



PulverizR™ PDC Bits

Thru Tubing		Plug Millout					Formation		
1.7", 1.85"	2", 2.25"	2.75"	3.625", 3.75", 3.875", 4", 4.125"	4.375"	4.5"	4.625", 4.75"	8.5"	12.25"	17.5"
8.5"	8.5"	6.58"	8.5"	8.831"	8.912"	8.422"	8.986"	10.793"	21.24"
3	3	5	6	7	7	7	6	6	8
3	3	5	6	7	7	7	6 nozzles	6 nozzles	11 nozzles
1" MT	1" MT	1-½" MT	2-3/8" PAC	2-3/8" REG	2-%" REG	2-3/8" REG	4-1⁄2" REG	6-5/8" REG	6-5/8" REG
308	308	511	611	711	711	711	616	616	816
Scale/Minerals	Scale/Minerals	Plugs	Plugs	Plugs	Plugs	Plugs	Formation	Formation	Formation
	1.7", 1.85" 8.5" 3 3 1" MT	1.7", 1.85" 2", 2.25" 8.5" 8.5" 3 3 3 1" MT 1" MT	1.7", 1.85" 2", 2.25" 2.75" 8.5" 8.5" 6.58" 3 3 5 3 1" MT 1" MT 1-½" MT 308 308 511	1.7", 1.85" 2", 2.25" 2.75" 3.625", 3.75", 3.875", 4", 4.125" 8.5" 8.5" 6.58" 8.5" 3 3 5 6 3 3 5 6 1" MT 1" MT 1-½" MT 2-¾" PAC 308 308 511 611	1.7", 1.85" 2", 2.25" 2.75" 3.625", 3.75", 3.875", 4", 4.125" 4.375" 8.5" 8.5" 6.58" 8.5" 8.831" 3 3 5 6 7 3 3 5 6 7 1" MT 1" MT 1-½" MT 2-¾" PAC 2-¾" REG 308 308 511 611 711	1.7", 1.85" 2", 2.25" 2.75" 3.625", 3.75", 3.875", 4'.4125" 4.375" 4.5" 8.5" 8.5" 6.58" 8.5" 8.831" 8.912" 3 3 5 6 7 7 3 3 5 6 7 7 1" MT 1" MT 1-½" MT 2-¾" PAC 2-¾" REG 2-¾" REG 308 308 511 611 711 711	1.7", 1.85" 2", 2.25" 2.75" 3.625", 3.75", 3.875", 4", 4.125" 4.375" 4.5" 4.625", 4.75" 8.5" 8.5" 6.58" 8.5" 8.831" 8.912" 8.422" 3 3 5 6 7 7 7 3" MT 1" MT 1-½" MT 2-¾" PAC 2-¾" REG 2-¾" REG 2-¾" REG 308 308 511 611 711 711 711 711	1.7", 1.85" 2", 2.25" 2.75" 3.625", 3.75", 4.375" 4.5" 4.625", 4.75" 8.5" 8.5" 8.5" 8.5" 8.831" 8.912" 8.422" 8.986" 3 3 5 6 7 7 7 7 6 6 6 3 3 3 5 6 7 7 7 7 6 6 nozzles 1" MT 1" MT 1-½" MT 2-¾" PAC 2-¾" REG 2-¾" REG 2-¾" REG 4-½" REG 308 308 511 611 711 711 711 616	1.7", 1.85" 2", 2.25" 2.75" 3.625", 3.75", 3.875", 4", 4.125" 4.5" 4.625", 4.75" 8.5" 12.25" 8.5" 8.5" 6.58" 8.5" 8.831" 8.912" 8.422" 8.986" 10.793" 3 3 5 6 7 7 7 6 6 6 3 3 3 5 6 7 7 7 6 nozzles 1" MT 1" MT 1-½" MT 2-¾" PAC 2-¾" REG 2-¾" REG 2-¾" REG 4-½" REG 6-¾" REG 308 308 511 611 711 711 711 616 616



Features

- Balanced design with general purpose cutting structure and cutter technology
- Optimized PDC cutter to minimize cutting size
- Drilling and Completions bits designed for specific applications
- Cutter types, layout and geometry are continuously evaluated for performance

Accessories

- WOS PowR Motors
- WOS High Flow Check Valves
- WOS AV Sub
- WOS Flex Sub
- BitSavR



SCAN CODE TO VIEW PRODUCT PAGE

MADE IN THE U.S.A.

 \star

Contact Sales: 346-774-4433 WOS.COM